



Crown RF
 2005-A Industrial Blvd.
 Rockwall, TX 75087

972-771-4711
 800-225-3429
 972-771-9499 (fax)

www.crownrf.com

sales@crownrf.com

LMR-400 / SW-400** Connector Special

** 3-PC Crimp	Description	Crown RF #	10-	25-	50-	100-
	N (M)	CRN-1601	4.61	3.88	3.39	2.95
	N (M) Solder/Crimp Rt. Angle	CRN-1690	7.46	6.95	6.27	5.31
	N (F) Crimp	CRN-1625	5.39	4.83	4.29	3.75
	BNC (M) Crimp	CRB-4000	5.54	4.89	4.22	3.67
	BNC (M) Solder/Crimp Rt. Angle	CRB-4090	6.93	6.45	5.61	4.96
	SMA (M) Crimp	CRS-9400	5.62	4.96	4.35	3.79
	SMA (M) Solder/Crimp Rt. Angle	CRS-9450	9.14	8.31	7.64	6.77
	TNC (M) Crimp	CRT-3400	5.37	4.48	3.96	3.37

Solderless EZ-Style Connectors

	Description	Crown RF # Times Microwave	10-	25-	50-	100-
	N (M) Crimp (solid cond. only)	CRN-1604QC EZ-400-NMH-X	9.55	8.90	8.21	7.45
	N (M) Crimp Rt. Angle ** can be used with LMR400 solid and LMR400UF stranded	CRN-1692QC (Due Dec. 2017)	10.70	9.94	9.31	8.47
	N (M) Crimp Rt. Angle (solid cond. only)	CRN-1691QC EZ-400-NMH-RA-X	10.95	10.24	9.56	8.74
	N (F) Crimp	CRN-1609QC EZ-400-NF-X	9.35	8.70	7.83	6.86

****Save \$ on Crown [SW-400](#) (=LMR-400) 500' - .67 / 1,000' - .62**

**** To view our complete line of LMR-400 Connectors [click here](#) ****