



CROWN RF



2005A Industrial Blvd., Rockwall, TX 75087 972-771-4711 800-225-3429 (fax) 972-771-9499

CABLE ATTENUATION (NOMINAL) CHART

Db LOSS PER 100ft.

PART #	150 MHz	450 MHz	900 MHz	1500 MHz	2000 MHz	2500 MHz
SW-195	4.4	7.8	11.1	14.5	16.9	19.0
LMR-195	4.3	7.5	10.7	13.4	16.1	18.1
SW-240	3.0	5.3	7.6	9.9	11.5	12.9
LMR-240	3.0	5.3	7.6	9.9	11.5	13.0
SW-400	1.5	2.7	3.9	5.1	6.0	6.8
LMR-400	1.5	2.7	3.9	5.1	6.0	6.8
BELDEN 9913	1.5 (100)	2.7 (400)	7.6	8.2 (1000)	-	21.5 (4K)
LMR-600	1.0	1.7	2.5	3.3	3.9	4.4
RG-58	5.6	10.0	13	19.1	22.4	25.3
RG-142	4.7	8.3	12.1	16.1	18.9	21.4
RG-213	2.5	4.6	6.9	9.3	11.1	12.7
RG-214	1.5	4.6	6.8	9.2	11.0	12.7
RG-223	4.9	8.7	12.7	16.8	19.7	22.3
RG-393	2.4 (100)	5.0 (400)	8.8 (1000)	-	-	-
RG-400	4.5 (100)	10.5 (400)	17.0 (1000)	-	-	-

- SW CABLES ARE MANUFACTURED BY COLEMAN CABLE
- 'LMR' IS A REGISTERED TRADEMARK OF TIMES MICROWAVE
- RG CABLES ARE MANUFACTURED PER MIL-SPEC