



# CROWN RF



2005A Industrial Blvd. Rockwall, TX 75087 972-771-4711 972-771-9499 (fax) 800-225-3429 (toll free)  
[sales@crownerf.com](mailto:sales@crownerf.com) [www.crownerf.com](http://www.crownerf.com)

## LMR-400 LOW LOSS CABLE

- High performance – 50 ohm
- UV Resistant PE (Polyethylene)
- Available in Waterproof or Riser Rated
- Manufactured by Times Microwave
- 100% sweep tested to 5.8 GHz
- 500' or 1000' spools (Weight: Appr. 68# / 1k')

## CONSTRUCTION INFORMATION

1	Conductor Size	10 Gauge
2	Conductor Type	Solid Bare Copper-Clad Aluminum
3	Conductor Diameter	.108"
4	Insulation Type	Extruded Foam Polyethylene
5	Insulation Diameter	.285"
6	Shield (Outer Cond.)	Aluminum Tape
7	Shield (Overall Braid)	Tinned Copper
8	Shield Diameter	.320" NOM
9	Shielding Effectiveness	90 dB
10	Jacket Type	Polyethylene
11	Temperature Range	-40 to +185°F
12	Voltage Withstand	2500 VDC (Peak Power – 16KW)
13	Jacket Color	Black
14	Jacket Diameter	.405" (Min Bend Radius – 1")
15	Impedance (OHMS)	50 OHMS
16	Capacitance (pF/ft.)	23.9 pF/ft
17	Velocity of Propagation	85%
18	DC Resistance	Inner Conductor 1.39 Ohm/1000' Outer Conductor 1.65 Ohm/1000'
19	Cutoff Frequency	16.2 GHZ

## Nominal Attenuation (db/100')

	<u>SW-400</u>	<u>LMR-400</u>	(Extra-Flex) <u>SW-400EF</u>	(Ultra-Flex) <u>LMR-400UF</u>
150MHz	1.5	1.5	1.8	1.8
450MHz	2.7	2.7	3.3	3.3
900MHz	3.9	3.9	4.7	4.7
1500MHz	5.1	5.1	6.2	6.2
2000MHz	6.0	6.0	7.2	7.2
2500MHz	6.8	6.8	8.1	8.1

Signa-Wave™ is a trademark of Coleman Cable Inc.  
LMR is a registered trademark of Times Microwave