



CROWN RF



2005A Industrial Blvd. Rockwall, TX 75087 972-771-4711 972-771-9499 (fax) 800-225-3429 (toll free)
sales@crownerf.com www.crownerf.com

RG-58 DATA SHEET


CONSTRUCTION PARAMETERS:

		<u>OD (in.)</u>
CONDUCTORS:	20 AWG (1/.032) SOLID BARE COPPER	0.031
DIELECTRIC:	SOLID POLYETHYLENE	0.114
SHIELDING:	95% TINNED COPPER BRAID	0.136
JACKET:	PVC (CL2)	0.195

ELECTRICAL PROPERTIES:

CONDUCTOR RESISTANCE:	10.5 OHMS /1,000 ft.
IMPEDANCE:	53.5 ohm
CAPACITANCE:	29 pF/ft
VELOCITY OF PROPAGATION:	66%

CABLE CROSS-SECTION



ATTENUATION:

(Max. db/100 ft):	100 MHz	4.4
	400MHz	8.5
	900 MHz	13

MISCELLANEOUS INFORMATION:

JACKET COLOR:	BLACK
FLAME RATING:	UL-1581 VERTICAL TRAY FLAME TEST
UL:	1354
MAX. TEMPERATURE RATING:	75° C
MAX. OPERATING VOLTS:	300 RMS / 30 RMS (UL AWM Style 1354)
** APPROX. WEIGHT (lb/1000ft):	28

*****THIS PRODUCT COMPLIES WITH EUROPEAN DIRECTIVE 2002/95/EC (RoHS)*****